

Specifications

Model		SKD-LRBK100FB	SKD-LRBK150FB	SKD-LRBK220B	
		SKD-LRBK100FW	SKD-LRBK150FW	SKD-LRBK220W	
Input Voltage		DC 40V			
Power Consumption (W)		150	150	150	
Torque	(N.m)	6~10	8~15	12~22	
Repeatable Torque Accuracy (%)		±5%			
Torque Adjustment		Stepless			
Free Speed (r.p.m)±10%		880	600	350	
Screw Size Dia(mm)	Machine Screw	≤8	≤10	≤10	
	Tapping Screw	≤6	≤8	≤8	

Specifications

Model		SKD-LRBK50B	SKD-LRBK75B	SKD-LRBK100B	SKD-LRBK150B
		SKD-LRBK50W	SKD-LRBK75W	SKD-LRBK100W	SKD-LRBK150W
Input Voltage		DC 40V			
Power Consumption (W)		100	120	120	150
Torque	(N.m)	2~5	3~7.5	6~10	8~15
Repeatable Torque Accuracy (%)		±5%			
Torque Adjustment		Stepless			
Free Speed (r.p.m) ±10%		1000	800	550	350
Screw Size Dia(mm)	Machine Screw	≤5	≤6	≤8	≤10
	Tapping Screw	≤4	≤4.5	≤6	≤8